

HANNES.G

JC171DP

# LCD Monitor



GO BEYOND

# LCD Monitor

|                            |                           |  |
|----------------------------|---------------------------|--|
| <b>LCD Panel</b>           | <b>Display size</b>       | 17" (43,18 cm)   |
|                            | Panel Type                | Active Matrix TFT  |
|                            | <b>Brightness</b>         | 300 cd/m <sup>2</sup> (typ.)                                     |
|                            | Contrast ratio            | 700:1 (typ.)   |
|                            | <b>Pixel pitch</b>        | 0.264(H)*0.264(V) mm   |
|                            | Resolution (H x V)        | SXGA 1280 x 1024   |
|                            | <b>Response time</b>      | 12 ms (typ.)   |
|                            | View angles LR,UD         | H/V 140°/130°  |
|                            | <b>Display colors</b>     | 16.2M Colors   |
|                            | Color                     | 9300K, 6500K, User Mode  |
|                            | <b>Display Surface</b>    | Anti-Glare   |
|                            | <b>Input</b>              | Input 1  |
| <b>Input 2</b>             |                           | DVI-D  |
| Input 3                    |                           |  |
| <b>Output</b>              | <b>Output 1</b>           |  |
|                            | Output 2                  |  |
|                            | <b>Headphone</b>          |  |
|                            | Speakers                  | 1 W x 2  |
| <b>Power</b>               | <b>Supply</b>             | AC 100~240V, 50~60Hz   |
|                            | Consumption               | 45 W (typ.)  |
| <b>Operating Condition</b> | <b>Temperature</b>        | 5 ~ 40°C   |
|                            | Humidity                  | 20 ~ 90%   |
| <b>Physical</b>            | <b>Dimension (W*D*H)</b>  | 369 x 212 x 402mm  |
|                            | Packing dimension (W*D*H) | 435 x 150 x 475mm  |
|                            | <b>Net weight</b>         | 4,4 kg   |
|                            | Gross weight              | 5,6 kg   |
|                            | <b>Tilt</b>               | 0 - 20°  |
|                            | Kensington Lock           | ✓  |
|                            | <b>VESA mounting</b>      | VESA Standard, 100mm   |
|                            | Front control             | Auto, Vol(-), Power/LED, Vol(+), Menu                            |
| <b>Controls</b>            | <b>On screen display</b>  | EN, SC, TC, DE, FR, IT, ES, JS, DU                               |
|                            | Safety                    | CE, FCC, BSMI, UL, TUV/GS, 3C                                    |
| <b>Certification</b>       | <b>Emission</b>           | TCO99  |
|                            | Power saving              | Energy Star  |
| <b>Extras 1</b>            |                           |  |
| <b>Extras 2</b>            |                           |  |
| <b>Extras 3</b>            |                           |  |
| <b>Accessories</b>         |                           | Power cord, VGA cable, Audio cable, CD Manual, Quick-Start Guide |

Specifications are subject to change without notice. Error accepted.



VESA Mounting



Digital / Analog Inputs



Built-In Stereo Speakers



1280x1024 Resolution

GO BEYOND